



APPLICATION
TRACTOR
4X4



BIAS ROW CROP

FARMING TYRES

- Excellent traction and directional stability.
- Deep lugs, low slip and optimized rubber compounds help reduce wear to give exceptionally long tire life.



GRIPKING R-1



GRIP QUEEN

SIZE	PATTERN	PLY RATING	RIM WIDTH	TT or TL	SECTION WIDTH		OVERALL DIAMETER		STATIC LOADED RADIUS		ROLLING CIRCUM ± 2.5 %		NSD		LOAD CAPACITY		INFLATION PRESSURE		LOAD INDEX	SPEED	
					mm	inch	mm	inch	mm	inch	mm	inch	mm	32nds	kg	lbs	bar	psi		kmph	mph
4.50-19	GRIPKING R-1	6	3.0	TT	122	4.8	736	29.0	343	13.5	2146	84.5	15	19	487	1071	4.5	64	83	A8/40kmph	A8/25mph
4.00-21	GRIPKING R-1	6	3.0	TT	115	4.5	762	30.0	350	13.8	2247	88.5	6	7	180	396	1.8	25	48	A8/40kmph	A8/25mph
4.00-21	GRIP QUEEN	6	3.0	TT	115	4.5	762	30.0	350	13.8	2247	88.5	6	7	180	396	1.8	25	48	A8/40kmph	A8/25mph
5.00-21	GRIPKING R-1	6	4.0	TT	140	5.5	823	32.4	360	14.2	2310	91.0	10	13	435	957	2.7	38	79	A8/40kmph	A8/25mph
8.3-28	GRIPKING R-1	8	7.0	TT	211	8.3	1095	43.1	533	21.0	3251	128.0	27	34	1000	2200	2.4	34	108	A8/40kmph	A8/25mph
9.5-28	GRIPKING R-1	8	8.0	TT	241	9.5	1156	45.5	543	21.4	3350	132.0	28	35	1180	2596	2.8	40	114	A8/40kmph	A8/25mph
4.00-30	GRIPKING R-1	4	3.0	TT	116	4.5	995	39.1	457	18.0	2938	115.7	12	15	350	770	1.3	18	72	A8/40kmph	A8/25mph
7.2-30	GRIPKING R-1	6	6.0	TT	183	7.2	1095	43.1	533	21.0	3225	126.9	27	34	690	1518	2.3	33	95	A8/40kmph	A8/25mph
9.5-30	GRIPKING R-1	8	8.0	TT	241	9.5	1200	47.2	559	22.0	3531	139.0	29	36	1215	2673	2.8	40	115	A8/40kmph	A8/25mph
8.3-32	GRIPKING R-1	8	7.0	TT	211	8.3	1193	47.0	584	23.0	3581	141.0	30	38	1090	2398	3.2	45	111	A8/40kmph	A8/25mph
9.5-32	GRIPKING R-1	8	8.0	TT	241	9.5	1255	49.4	584	23.0	3683	145.0	30	38	1060	2332	2.1	50	119	A8/40kmph	A8/25mph
4.00-36	GRIP QUEEN	6	3.0	TT	120	4.7	1140	44.9	524	20.6	3364	132.5	6	7	375	825	2.4	34	74	A8/40kmph	A8/25mph
4.00-36	GRIPKING R-1	6	3.0	TT	120	4.7	1140	44.9	524	20.6	3364	132.5	12	15	375	825	2.4	34	74	A8/40kmph	A8/25mph
4.50-36	GRIPKING R-1	6	3.0	TT	135	5.3	1150	45.2	530	20.9	3402	134.0	12	15	450	990	2.5	35	80	A8/40kmph	A8/25mph
5.00-36	GRIPKING R-1	6	3.0	TT	145	5.7	1175	46.2	540	21.3	3456	136.0	12	15	460	1012	2.5	35	81	A8/40kmph	A8/25mph
7.2-36	GRIPKING R-1	8	6.0	TT	183	7.2	1255	49.4	610	24.0	3810	150.0	30	38	1005	2211	3.7	53	108	A8/40kmph	A8/25mph
8.3-36	GRIPKING R-1	8	7.0	TT	211	8.3	1293	50.9	610	24.0	3810	150.0	28	38	1150	2530	3.2	45	113	A8/40kmph	A8/25mph
9.5-36	GRIPKING R-1	8	8.0	TT	241	9.5	1359	53.5	623	24.5	4000	157.5	31	39	1500	3300	3.6	51	112	A8/40kmph	A8/25mph
12.4-36	GRIPKING R-1	8	11.0	TT	315	12.4	1465	57.7	686	27.0	4318	170.0	28	35	1750	3850	2.3	33	127	A8/40kmph	A8/25mph
8.3-38	GRIPKING R-1	8	7.0	TT	211	8.3	1350	53.1	621	24.5	3986	157.0	31	39	1250	2750	3.5	50	116	A8/40kmph	A8/25mph
9.5-38	GRIPKING R-1	8	8.0	TT	241	9.5	1405	55.3	646	25.5	4147	163.3	31	39	1800	3960	3.0	43	128	A8/40kmph	A8/25mph
11.2-38	GRIPKING R-1	6	10.0	TT	284	11.2	1465	57.7	693	27.2	4343	171.0	30	38	1295	2850	1.8	26	117	A8/40kmph	A8/25mph
12.4-38	GRIPKING	8	11.0	TT	315	12.4	1511	59.4	716	28.2	4496	177.0	32	40	1750	3850	2.7	38	127	A8/40kmph	A8/25mph
	GRIPKING	12	11.0	TT	315	12.4	1511	59.4	716	28.2	4496	177.0	32	40	1800	3960	2.8	39	128	A8/40kmph	A8/25mph