



APPLICATION
EARTH MOVER



EARTHMOVER TYRES

- The special non-directional tread design formulated with silica based tread compound, together with a heavy duty nylon carcass makes it capable of withstanding cuts, snags and bruises under all service conditions.



SIZE	PATTERN	PLY RATING	RIM WIDTH	TT or TL	SECTION WIDTH		OVERALL DIAMETER		STATIC LOADED RADIUS		ROLLING CIRCUM ± 2.5 %		NSD		LOAD CAPACITY		INFLATION PRESSURE		LOAD INDEX	SPEED	
			inch		mm	inch	mm	inch	mm	inch	mm	inch	mm	32nds	kg	lbs	bar	psi		kmph	mph
9.00-20	ROCK LUG	18	7.5	TT	259	10.2	1035	40.7	476	18.7	3056	120.3	18	23	2260	4972	7.0	99	136	B/50 kmph	B/30mph
10.00-20	ROCK LUG	20	8.0	TT	274	10.8	1075	42.3	494	19.4	3171	124.8	18	23	2750	6050	7.6	109	143	B/50 kmph	B/30mph
14.00-24	ROCK LUG	24	10.0	TL	373	14.7	1368	53.8	635	25.0	4039	159.0	25	31	9500	20900	8.6	124	186	A2/10kmph	A2/6mph
16.9-24	ROCK LUG	12	15.0	TL	460	18.1	1310	52.5	584	23.0	3785	149.0	26	32	3257	7165	2.6	38	149	A2/10kmph	A2/6mph
17.5L-24	ROCK LUG	12	15.0	TL	462	18.2	1280	50.0	559	22.0	3683	145.0	26	32	3908	8598	3.3	48	155	A2/10kmph	A2/6mph
14.00-25	ROCK LUG	24	10.0	TL	375	14.8	1374	54.1	635	25.0	4039	159.0	25	31	9500	20900	8.6	124	186	A2/10kmph	A2/6mph
15.5-25	ROCK LUG	12	12.0	TL	394	15.5	1278	50.3	569	22.4	3658	144.0	25	31	5600	12320	4.0	58	168	A2/10kmph	A2/6mph
15.5-25	ROCK LUG	16	12.0	TL	394	15.5	1278	50.3	569	22.4	3658	144.0	25	31	6250	13750	4.5	101	168	A2/50kmph	A2/30mph
17.5-25	ROCK LUG	16	14.0	TL	432	17.0	1344	52.9	635	25.0	3955	156.0	28	35	7300	16060	3.0	44	158	A2/50kmph	A2/30mph
17.5-25	ROCK LUG	20	14.0	TL	432	17.0	1344	52.9	635	25.0	3955	156.0	28	35	8250	18150	4.0	58	164	B/50 kmph	B/30mph
20.5-25	ROCK LUG	16	17.0	TL	531	20.9	1486	58.5	686	27.0	4394	173.0	31	39	8268	18190	2.7	40	167	B/50 kmph	B/30mph
20.5-25	ROCK LUG	20	17.0	TL	531	20.9	1486	58.5	686	27.0	4394	173.0	31	39	9520	20944	3.2	47	170	B/50 kmph	B/30mph
23.5-25	ROCK LUG				UNDER DEVELOPMENT																



APPLICATION
FORK LIFT

INDUSTRIAL FORKLIFT TYRES

- Premium tyre, designed for heavy duty service on forklift trucks, material handling & mining equipment.
- The deep tread, extra hick sidewalls & touch casing provide exceptional durability & minimize the risk of punctures & accidental damages.
- Silica & natural rubber in tread compound provides greater chip and rear resistance.
- Specially designed rim guard ensures protection against flats & wheel damages in the rim flange area



SIZE	PATTERN	PLY RATING	RIM WIDTH	TT or TL	SECTION WIDTH		OVERALL DIAMETER		NSD		LOAD CAPACITY		INFLATION PRESSURE		LOAD INDEX	SPEED	
			inch		mm	inch	mm	inch	mm	32nds	kg	lbs	bar	psi		kmph	mph
4.80/4.00-8	LIFTKING HD	8	3.0	TT	117	4.6	414	16.3	7	9	530	1166	10.2	145	86	A5/25 kmph	A5/16mph
5.70/5.00-8	LIFTKING HD	10	3.0	TT	132	5.2	467	18.3	7	9	1415	3113	10.2	145	121	A5/25 kmph	A5/16mph
6.90/6.00-9	LIFTKING HD	10	4.0	TT	160	6.3	540	21.2	10	13	1715	3773	8.7	124	126	A5/25 kmph	A5/16mph
6.50-10	LIFTKING HD	12	5.0	TT	178	7.0	595	23.4	11	14	2180	4796	9.9	141	135	A5/25 kmph	A5/16mph
7.00-12	LIFTKING HD	14	5.0	TT	180	7.1	690	27.1	12	15	2750	6050	9.2	131	143	A5/25 kmph	A5/16mph
23x5	LIFTPOWER	10	4.0	TT	155	6.1	635	25.0	10	13	1985	4367	8.0	114	132	A5/25 kmph	A5/16mph
7.00-15	LIFTKING HD	12	5.5	TT	201	7.9	749	30.4	16	20	3075	6765	8.8	125	147	A5/25 kmph	A5/16mph
7.50-15	LIFTKING HD	14	6.0	TT	211	8.3	772	28.3	14	18	3436	7559	10.0	142	146	A5/25 kmph	A5/16mph
28x9-15	LIFTKING HD	14	7.0	TT	213	8.4	720	33.7	16	20	3770	8294	9.0	128	154	A5/25 kmph	A5/16mph
8.25-15	LIFTKING HD	16	6.5	TT	239	9.4	855	33.6	14	18	3900	8580	9.2	131	152	A5/25 kmph	A5/16mph
10.00-20	ROCKPLUS HD	18	7.5	TT	284	11.2	1080	42.5	30	38	6900	15180	10.2	145	175	A5/25 kmph	A5/16mph
12.00-20	ROCKPLUS HD	20	8.5	TT	320	12.6	1151	45.3	34	43	9250	20350	10.2	145	185	A5/25 kmph	A5/16mph